

## SD71H – 600TVL CMOS Mini Dome Camera



**600TVL**

**1/3" CMOS**

**2D-DNR**

### Features

- 600TVL Latest CMOS Sensor
- 2.9 / 3.8 / 6 / 8 / 12mm Fixed Lens
- 2D-DNR
- Day&Night by Color Kill
- Wide Voltage input : DC6 – 20V
- OSD Control (Option)
- OSD Functions :
  - AGC : x4, x8, x16, x32
  - WB Mode : ATW, Indoor, Outdoor
  - D&N : Auto, Color
  - Brightness, Color, Contrast : 1~10
  - DNR : Level 1~3
  - Mirror : None, H, V, HV

### SPECIFICATION

Model	SD71H
Image Sensor	1/3" Progressive Scan CMOS Sensor
Resolution	600TVL , Effective Pixels 756(H)x504(V)
Shuttle	1/50s ~ 1/600,000s
Lens	M12 2.9 / 3.8 / 6 / 12mm Fixed Lens
Video Output	1Vp-p Video Composite
Day & Night	Color Kill
Minimum Illumination	0.1 Lux (@F1.2, 30IRE)
S/N Ratio	>58 DB
Gamma	0.45
Sync	Internal
Working Environment	-30° ~ +80°C, <90° Humidity (Non-Condensing)
Power	12VDC, Max. 1.15W
Dimension	106mm(φ) x 72mm(H), 150g

\* Specification maybe changed without prior notice